ETA USB Charger

Type C: 60W

FEATURES



- Dual USB-A and USB-C outputs for fast charging and broad device compatibility
- Smart protocol detection for Android and iOS devices
- Compatible with 12V and 24V vehicle systems
- High efficiency up to 94% with low output ripple
- Comprehensive protection against overcurrent, overtemperature, short circuit, and more
- Wide operating temperature range from -10℃ to 60℃
- UL 94 V-0 flame-retardant rating

Model	ETA
Electrical	
Input Voltage Range (V)	9 ~ 31
Output (USB Type-A)	Max 24W: 5V / 3A, 9V / 2.67A, 12V / 2A Charging protocol: AFC, SCP, FCP, QC, BC1.2 (Apple 2.4A)
Output (USB Type-C)	Max 60W: 5V / 3A, 9V / 3A, 12V / 3A, 15V / 3A, 20V / 3A Charging protocol: PPS, PD, AFC, SCP, FCP, QC
Dual Outputs (USB Type-A + USB Type-C)	Max 24W: 5V / 4.8A (Double outputs: USB Type-A + USB Type-C)
Efficiency (%)	94
Others	
Operating Temperature (℃)	-10 ~ 60
Flame-Retardant Rating	UL 94 V-0
Input Terminal	6.3mm push-in flat blade terminal
Dimensions (mm)	39.40 × 35.75; Hole 30